




ETHERLINE® Cat.7 FLEX

Flexible use



Info

- Space-saving installation due to small cable diameters
- Cat.7 qualified for 10Gbit/s

Benefits

- Can be used in dry or damp rooms
- Screened against interference
- Can be used for Industrial Ethernet in harsh industrial environments
- 4pair: 100Mbit/s up to 10 Gbit/s for Industrial Ethernet

Application range

- Wiring of machines, tools, devices, appliances and control cabinets
- Max. cable length for 100 Mbit/s is 60 m
max. cable length for 10 Gbit/s is 60 m
- Suitable for EtherCAT and EtherNet/IP applications

Product features

- PUR outer sheath is highly resistant to mineral oils and abrasion
- Robust, halogen-free outer sheath
- High-quality, double screening ensures high transmission reliability in areas with electromagnetic interference

Norm references / Approvals

- Electrical requirements acc. to IEC 61156-6
- AWM certification for USA and Canada
- UL AWM Style 21576
- Flame retardant acc. to IEC 60332-1-2

Product Make-up

- Stranded conductor, bare, 7-wire
- Core insulation made of polyethylene (PE)
- S/FTP: copper braid as overall screening and pair screening with aluminium compound foil
- Outer sheath made of PUR
- Colour: green (based on RAL 6018)

Technical data

Classification ETIM 5/6
 ETIM 5.0/6.0 Class-ID: EC000830
 ETIM 5.0/6.0 Class-Description: Data cable

Peak operating voltage
 (not for power applications) 125 V

Minimum bending radius
 Fixed installation: 4 x outer diameter
 Flexing: 10 x outer diameter

Characteristic impedance
 nom. 100 Ω acc. to IEC 61156-6

Temperature range
 Fixed installation: -50°C to +80°C
 Flexing: -40°C to +80°C

Article number	Number of pairs and AWG per conductor	Core diameter in mm	Outer diameter [mm]	Copper index (kg/km)
ETHERLINE® Cat.7 FLEX				
2170934	4x2xAWG26/7	1	6.4	28

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Accessories

- EPIC® DATA AX RJ45 Cat.6_A refer to page 459
- EPIC® DATA 90 RJ45 Cat.6_A refer to page 459
- EPIC® DATA AX RJ45 Cat.6_A IP68 refer to page 460
- EPIC® DATA M12X refer to page 462
- EPIC® DATA CCR FA refer to page 463