KEL-FA split multi cable entry frames

for cables with connectors, tool-free assembly / IP54 / UL Type 12



The KEL-FA range is a compact system to route and seal pre-terminated cables as well as conduits or pneumatic hoses utilising KT series grommets. After populating the entry frame with grommets and cables, the cover is put on and the two clamping levers are locked with the lower part by pressing them down. The twist-proof construction of the KEL-FA enables intuitive assembly. Routing and sealing with IP54 / UL Type 12 for cable diameters from 1 to 35 mm.

The KEL-FA frames match exactly the cut-out dimensions for 10-, 16- and 24-pin standard industrial connectors. These KEL-FA frames can either be screw mounted or simply snapped into the KEL-SNAP frame.

Specifications

IP rating (EN 60529)	IP54	Integrated sealing	
UL Type (UL 50E)	UL Type 12	 Quick assembly without tools Strain relief according to EN 62444 (when using KT single hole grommets) 	
Material	Polyamide	Very high cable density with multi-hole grommets	
Flame class	UL94-V0, self-extinguishing	High flexibility with multi-range grommets and the IMAS-CONNECT™ system	
Operating temperature	-40 C° to 140 C°	 Warranty on pre-terminated cables remains Retrofits, repairs and maintenance can be done much more easily and quickly 	
Properties	UV-resistant, silicone free, anti- corrosive, halogen free	Wide variety	
Mounting options	Screw type mounting,Snap-in with KEL-SNAP		

Product types & sizes

KEL-FA 24|10 Part No. 55241 Height 22 mm EAN 4251269324796 Mounting height 22 mm Package quantity 10 Cut-out size 112 × 36 mm For max. no. of cables 40 No. of screw holes 4 Max. cable diameter 15 mm Diam. of screw holes 6 mm 147 mm 10 x KT small Length Suitable for grommets Width 62 mm

KEL-FA 24|4



Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets

Advantages & benefits

22 mm 22 mm 112 × 36 mm 4 6 mm 2 x KT small 2 x KT large

KEL-FA 24 7	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	55247 4251269324802 10 25 35 mm 147 mm 62 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets	22 mm 22 mm 112 × 36 mm 4 6 mm 6 x KT small 1 x KT large
KEL-FA 16 8	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	55168 4251269324826 10 32 15 mm 120 mm 62 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets	22 mm 22 mm 86 × 36 mm 4 6 mm 8 x KT small
KEL-FA 16 5	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	55165 4251269324833 10 17 35 mm 120 mm 62 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets	22 mm 22 mm 86 × 36 mm 4 6 mm 4 × KT small 1 × KT large
KEL-FA 16 2	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	55162 4251269324840 10 2 35 mm 120 mm 62 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets	22 mm 22 mm 86 × 36 mm 4 6 mm 2 x KT large
KEL-FA 10 6	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	55216 4251269324857 10 24 15 mm 100 mm 62 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets	22 mm 22 mm 65 × 36 mm 4 6 mm 6 x KT small
KEL-FA 10 3	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width	55212 4251269324864 10 9 35 mm 100 mm 62 mm	Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets	22 mm 22 mm 65 × 36 mm 4 6 mm 2 x KT small 1 x KT large